

# CertainTeed Sand Micro™

## Performance Series Mineral Fiber Ceilings

### Features:

- Special pulverized-marble aggregate coating provides rugged durability.
- Offers upscale look with additional durability and resists sagging.
- Designed for conditions where high temperatures and high humidity exist.
- Lightly textured surface provides attractive finish with excellent light reflectance and durability.
- Micro perforated for sound absorption.
- No added formaldehyde.

See reverse side for additional product specifications.

ITEM NUMBER	NOMINAL SIZE* (Inches)	EDGE DETAIL	UL CLASSIFIED		LR	RECYCLED CONTENT %
			NRC	CAC		
<b>SAFETONE® CLASS A</b>						
<b>SHM-150</b>	24 x 24 x 5/8	Narrow Reveal	<b>0.50</b>	<b>33</b>	0.88	<b>45</b>
<b>SHM-154</b>	24 x 24 x 5/8	Reveal	<b>0.50</b>	<b>33</b>	0.88	<b>45</b>
<b>SHM-157</b>	24 x 24 x 5/8	Trim	<b>0.50</b>	<b>33</b>	0.88	<b>45</b>
<b>SHM-190</b>	24 x 48 x 5/8	Narrow Reveal	<b>0.50</b>	<b>35</b>	0.88	<b>45</b>
<b>SHM-194</b>	24 x 48 x 5/8	Reveal	<b>0.50</b>	<b>35</b>	0.88	<b>45</b>
<b>SHM-197</b>	24 x 48 x 5/8	Trim	<b>0.50</b>	<b>35</b>	0.88	<b>45</b>

ASTM E 1264 Classification: Type III, Form 2, Pattern C E

\* Metric sizes available



### Popular Applications:


- Education • Retail • Malls • Offices • Healthcare
- Restaurants • Airports • Reception Areas




**BioShield™**  
BioShield™ treatment **included** for added mold and mildew resistance.




### Edge Details:




**TRIM EDGE**  
(Square) 1/8" Grid



**REVEAL EDGE**  
(Beveled) 1/8" Grid



**NARROW REVEAL EDGE**  
(Corner Bevel) 1/8" Grid



**NARROW REVEAL EDGE**  
(Corner Bevel) 1/8" Grid (Bolt Slot)

# PRODUCT SPECIFICATION DETAILS

## ACOUSTICAL CEILINGS

### 09 51 00

---

## PART 2: PRODUCTS

### 2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

### 2.2 MATERIALS

#### Standard Sizes:



24"x 24"



24"x 48"

Acoustical Ceiling Units:

1. Type III
2. Form 2
3. Pattern C E
4. Micro perforated wet-felted lay-in panel
5. Size 5/8" thick x [24" x 24"] [24" x 48"]
6. Edge Detail [Trim (Square)] [Narrow Reveal (Corner Bevel)] [Reveal (Beveled)]
7. Noise Reduction Coefficient (NRC) .50
8. Ceiling Attenuation Class (CAC) [33] [35]
9. Light Reflectance Coefficient (LR) .88
10. Recycled Content 45
11. Color White
12. Flame Spread Classification (ASTM E 84, CAN/ULC-S102M) Class A
13. Manufacturer, subject to compliance with requirements of this specification, CertainTeed Ceilings
14. Product Name Sand Micro™

---

Distributed by:

## ASK ABOUT OUR OTHER CERTAINTEED PRODUCTS AND SYSTEMS:

**EXTERIOR:** ROOFING • SIDING • WINDOWS • FENCE • RAILING • TRIM • DECKING • FOUNDATIONS • PIPE  
**INTERIOR:** INSULATION • GYPSUM • CEILINGS

---

CertainTeed Corporation  
P.O. Box 860  
Valley Forge, PA 19482

Professional: 800-233-8990  
Consumer: 800-782-8777  
[www.certainteed.com](http://www.certainteed.com)

**CertainTeed** 

Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. CertainTeed assumes no responsibility for the effects of structural movement.

™ © CertainTeed and the tag line "Quality made certain. Satisfaction guaranteed." are trademarks of CertainTeed Corporation. All other trademarks are the property of its affiliates and related companies.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

©08/09 CertainTeed Corporation.

CTC-4869