

A COMPLETE LINE OF SHINGLE UNDERLAYMENTS

ROOFERS' SELECT™ Made to order for the true professional

Contractors across the country told us what they wanted in a high quality shingle underlayment. We've taken new technology and created Roofers' Select™, an underlayment with high performance features which exceed No. 15 organic felt and are comparable to No. 30 organic felt.

Features

- Lays flat and is extremely resistant to wrinkling.
- Reduces the likelihood of slipping for increased safety.
- Doesn't tear away from fasteners when walked on or in strong winds.
- Meets underlayment requirements for the CertainTeed Integrity Roof System™.

Technical Data

Roll size (sq. ft.)	432 (4 squares)
Roll coverage (sq. ft.)	400
Roll length (ft.)	144
Roll width (ft.)	3
Shipping weight (approx. lbs./roll)	44

Manufactured to meet all performance requirements of ASTM D226 and ASTM D4869, including resistance to "liquid water transmission."
Manufactured to comply with ASTM D6757. Classified by UL to be a suitable underlayment for use in any UL Class A, B, or C fire-rated shingle system.



ROOFWRAP™ 15 / ROOFWRAP™ 30

UL classified for fire-rated shingle systems

RoofWrap™ 15 and RoofWrap™ 30 are asphalt-impregnated underlayments that meet key industry performance criteria, including ASTM D226 and ASTM D4869, and are UL classified for fire-rated shingle systems. They provide a water-resistant layer beneath roofing shingles and wood shakes, and meet underlayment requirements for the Integrity Roof System.

Technical Data

	RoofWrap 15	RoofWrap 30
Roll size (sq. ft.)	432 (4 squares)	216 (2 squares)
Roll coverage (sq. ft.)	400	200
Roll length (ft.)	144	72
Roll width (ft.)	3	3
Shipping weight (approx. lbs./roll)	53	56
ASTM D226	Type I	Type II
ASTM D4869	Type I	Type II
Underwriters Laboratories, Inc. (UL)	Type 15	Type 30

Both products are classified by UL to be a suitable underlayment for use in any UL Class A, B, or C fire-rated shingle system.



SHINGLEFELT™ 15 / SHINGLEFELT™ 30

A basic underlayment

ShingleFelt™ 15 and ShingleFelt™ 30 utility-grade underlayments comply with the important ASTM D4869 standard, yet are lighter and more economical than competing products. They provide a water-resistant layer beneath roofing shingles and wood shakes.

Technical Data

	ShingleFelt 15	ShingleFelt 30
Roll size (sq. ft.)	432 (4 squares)	216 (2 squares)
Roll coverage (sq. ft.)	400	200
Roll length (ft.)	144	72
Roll width (ft.)	3	3
Shipping weight (approx. lbs./roll)	39	28
ASTM D4869	Type I	Type I



For more information visit www.certainteed.com or call 1-800-233-8990

